



# Scotch™ Tape 3434

## Performance Auto Refinish Masking Tape

### Product Information

3/96

### Product Description / Markets

Scotch™ Tape 3434 is a light blue colored smooth creped paper masking tape that can be used for most all of the auto repair market paint masking operations.

Features	Advantages	Benefits
<ul style="list-style-type: none"><li>* Latex saturated heavy weight smooth creped paper backing</li></ul>	<ul style="list-style-type: none"><li>* Excellent solvent resistance</li><li>* Good water resistance</li><li>* Good conformability</li><li>* Excellent edge tear resistance</li><li>* Excellent sliver resistance</li><li>* Easy hand tear</li><li>* Smoothness</li></ul>	<ul style="list-style-type: none"><li>* Prevents paint bleed through</li><li>* No need to re-mask after wet sanding</li><li>* Performs well with water based paint systems</li><li>* Better curve masking</li><li>* Prevents tearing in curves or on difficult surfaces</li><li>* Easy one piece removal</li><li>* Better handling</li><li>* Reduces finger abrasion</li><li>* Good paint line</li></ul>
<ul style="list-style-type: none"><li>* Light blue color</li></ul>	<ul style="list-style-type: none"><li>* Good contrast</li></ul>	<ul style="list-style-type: none"><li>* Easy recognizable with masking paper</li></ul>
<ul style="list-style-type: none"><li>* Crosslinked rubber resin adhesive</li></ul>	<ul style="list-style-type: none"><li>* Excellent instant adhesion</li><li>* Excellent holding power</li><li>* Good adhesive transfer resistance</li><li>* Controlled unwind</li></ul>	<ul style="list-style-type: none"><li>* Sticks easily</li><li>* Resists lifting even in repeat bake cycles</li><li>* Clean removal</li><li>* Easy handling</li></ul>

### Applications / Performance

The Scotch™ Tape 3434 provides outstanding painting results with common two component paint systems as well as with water based paint systems. This product possesses a temperature resistance of 110 °C and as a consequence will meet all the requirements of every application in a body shop.

# Scotch™ Tape 3434

## Product Characteristics

Thickness	:	0.180 mm	AFERA 4006
Adhesion to steel	:	10 N/25 mm	AFERA 4001
Tensile strength	:	115 N/25 mm	AFERA 4004
Elongation	:	10.5 %	AFERA 4005
Temperature performance	:	110 °C	

Satisfactory performance and clean removal of Scotch™ Tape 3434 will be achieved at varying temperatures/time exposure on many substrates. Tests should be conducted to establish Scotch™ Tape 3434 performance parameters in your process conditions. The optimum level for product performance and easy removal is at 110 °C for 60 min.

## Available Sizes

Width (mm)	:	15, 19, 25, 30, 38, 50 and 75
Length (m)	:	50

## Storage Conditions

Store in clean dry place. Temperature of 21 °C and 50 percent relative humidity are recommended.

## Disclaimer

All statements, technical information and recommendations are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed. Please ensure before using our products that it is suitable for your intended use. All questions of liability relating to this products are governed by the Terms of Sale subject, where applicable, to the prevailing law.

## Masking and Packaging Systems Division

3M Europe  
Masking & Packaging Systems Division  
Hermeslaan 7  
B - 1831 Diegem  
Tel: ++32-2-722.45.50  
Fax: ++32-2-722.45.18

