

September, 2011

3M™ Double Coated Removable Foam Tape 4658F

Product Description

3M™ Double Coated Removable Foam Tape 4658F is a clear, double coated acrylic foam tape that removes cleanly from many surfaces. 3M™ Adhesive 100 is a firm acrylic adhesive system that offers high ultimate bond strength, good temperature resistance, solvent resistance and static shear holding power. 3M tape 4658F can reach high bond strengths and some high surface energy substrates and may become difficult to remove.



Technical Information Note

The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

Typical Physical Properties

Property	Values		Test Name
Color	Clear		
Thickness: Nominal	0.8 mm	31 mil	
Thickness Tolerance	± 10 %		
Adhesive Type	100		
Foam Type	Acrylic		
Foam Density	960 kg/m ³	60 lb/ft ³	
Liner	Polyester Film		
Liner Color	Clear		Primary
Liner Thickness	0.08 mm	3 mil	

Typical Performance Characteristics

Property	Values		Test Condition	Method	Test Name	Dwell/Time	Dwell/Time Units	Temp C	Temp F	Environmental Conditions	Substrate	Backing	Notes
	1	2											
Short Term Temperature Resistance	100 °C	212 °F	Short Term										
Long Term Temperature Resistance	80 °C	175 °F	Long Term										

Table continued on next page

Typical Performance Characteristics (continued)

Property	Values		Test Condition	Method	Test Name	Dwell Time	Dwell Time Units	Temp C	Temp F	Environmental Condition	Substrate	Backing	Notes
Solvent Resistance	No apparent degradation when exposed to splash testing of most hydrocarbon solvents.												
UV Resistance	Excellent resistance to direct exposure to sunlight or other sources of ultraviolet (U.V.) light.												
90° Peel Adhesion Stainless Steel	240 oz/in 26.3 N/cm			ASTM D3330	90° Peel Adhesion	72	hr	23C	72F	50%RH	Stainless Steel	2 mil PET	12 in/min (300 mm/min)

Typical Performance Characteristics (continued)

Static Shear	Test Condition
1000 g	Room Temperature
750 g	@ 49°C (120°F)
500 g	@ 70°C (158°F)

Property: Static Shear
 Method: ASTM D3654
 notes: 1/2 in x 1 in sample size; Test terminated at 10,000 min

Available Sizes

Property	Values	
Maximum Length	160 m	175 yd
Maximum Available Width	1.18 mm	46.5 in
Normal Slitting Tolerance	±0.8 mm	±1/32 in

Available Sizes

1/2 in x 27 yd (12 mm x 25 m)
 3/4 in x 27 yd (19 mm x 25 m)
 1 in x 27 yd (25 mm x 25 m)

Design Considerations

- As a general rule, four square inches of tape should be used for each pound of weight to be supported in static load. More or less tape may be required depending upon the particular application. User evaluation is, therefore, required to determine optimal tape usage.
- Care should be used when bonding to surfaces with very low internal strength such as painted plaster board, fabric or cloth, wallpaper, blown vinyl, etc. since delamination of that surface may occur.
- Care should also be taken with wood veneers and highly polished wood as very glossy surfaces may leave an image when the tape is removed.

Handling/Application Information

Application Examples

- Signs
- Holding Electronic Accessories
- Exhibitions
- Smoke Alarms
- Dispensers
- Air Fresheners
- Point of Purchase and other Displays
- Nameplates
- Picture Frame Tabs

3M™ Double Coated Removable Foam Tape 4658F

Handling/Application Information (continued)

Application Techniques

- Bond strength is dependent upon the amount of adhesive-to-surface contact developed. Firm application pressure helps develop better adhesive contact and improve bond strength.
- To obtain optimum adhesion, the bonding surfaces must be clean, dry and well unified. Typical surface cleaning solvents are isopropyl alcohol (rubbing alcohol) and water or heptane. Note: Carefully read and follow manufacturer's precautions and directions for use when using solvents.
- Ideal tape application temperature is 70°F to 100°F (21°C to 38°C). Initial tape application to surfaces at temperatures below 50°F (10°C) is not recommended because the adhesive may become too firm to adhere readily. However, once properly applied, low temperature holding is generally satisfactory.

Removal Techniques:


For rigid surfaces, lever or pry apart the substrates to break the bond.



For flexible surfaces, peel back slowly to ensure clean removal.



To remove tape from substrate, pull back corner and peel off quickly.



Storage and Shelf Life

Product retains its performance and properties for 24 months from date of manufacture when stored in original cartons at 70°F (21°C) and 50% relative humidity.

Trademarks

3M is a trademark of 3M Company.

References

Property	Values
3m.com Product Page	https://www.3m.com/3M/en_US/company-us/all-3m-products/-/3M-Double-Coated-Removable-Foam-Tape-4658/?N=5002385+3293242748&rt=rud
Safety Data Sheet SDS	https://www.3m.com/3M/en_US/company-us/SDS-search/results/?gsaAction=msdsSRA&msdsLocale=en_US&co=ptn&q=4658F

ISO Statement

This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9001 standards.

Information

Technical Information: The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

Product Selection and Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.

Disclaimer: 3M industrial and occupational products are intended, labeled, and packaged for sale to trained industrial and occupational customers for workplace use. Unless specifically stated otherwise on the applicable product packaging or literature, these products are not intended, labeled, or packaged for sale to or use by consumers (e.g., for home, personal, primary or secondary school, recreational/sporting, or other uses not described in the applicable product packaging or literature), and must be selected and used in compliance with applicable health and safety regulations and standards (e.g., U.S. OSHA, ANSI), as well as all product literature, user instructions, warnings, and limitations, and the user must take any action required under any recall, field action or other product use notice. Misuse of 3M industrial and occupational products may result in injury, sickness, or death. For help with product selection and use, consult your on-site safety professional, industrial hygienist, or other subject matter expert. For additional product information, visit www.3M.com.

